

SkyRC T100 Dual Output Charger



SK-T100

Rating: Not Rated Yet
Price
Sales price R1399,00

[Ask a question about this product](#)

Manufacturer [SkyRC](#)

Description

- SkyRC T100 is a twin-channel charger with two independent circuits which can charge batteries of varying chemistries (LiPo / LiFe / LiIon / LdHV / NiMH / NiCd / Pb) simultaneously.
- Its sleek design allows easy front-loading plug-in convenience of balancing and XT60 ports. It is not only compact in size but also powerful in output with maximum 100W charging power and 5A charging current which makes charging more sufficient. With the new AGM and cold charge modes, the user is free to charge their Pb and AGM batteries in cold days.
- Twin-channel charger
- SkyRC T100 allows you to plug 2 batteries into one charger simultaneously, and it will intelligently and automatically initiate the charging of 2 batteries at once to their maximum capacity. To top it off, the batteries being charged do not even need to have the same configuration. You can connect different chemistry(NiMH / NiCd / LiPo / LiFe / LiIon / LdHV / Pb)batteries into any of the charging ports.
- Specs
- Twin-channel charger with two independent circuits which can charge batteries of varying chemistries (LiPo / LiFe / LiIon / LdHV / NiMH / NiCd / Pb) simultaneously.
- For Pb battery, AGM Charge and Cold Charge mode are available.
- Size and Weight
- Case Material: Plastic
- Case Size: 90x105x177mm
- Weight: 300g
- Material
- Type: D16LCD
- Display Backlight: Blue
- Power
- Input Voltage: AC 100-240V
- Charge Voltage: 200V/2
- Battery Types:Cells
- Max Output: about 6V, 2.4 cells
- With NiCd, Li-Ion, etc.
- Re-BLTV
- Battery Capacity Range
- LiPo/LiIon/LiFe/LdHV:100-5000mAh
- NiMH/NiCd:100-5000mAh
- Pb: 100-8000mAh
- Charge Voltage

Chargers: SkyRC T100 Dual Output Charger

Input: 4.18-4.25V/pc

Input: 1.5A-3.1V/pc

Input: 4.08-4.2V/pc

CCV: 4.25-4.35V/cell(NiMH/NiCd) Delta peak detection: 3.15mV/cell - Default: 4mV/cell

Charge Current: 0.1A-5.0A

Balance Cuts: 2-4 cells

Balance Current: 500mA/cell

Safety Timer: 1-999minutes and Off

Charge Method:CC/CV for Li/Iron batteries

Delta-peak Sensitivity for NiMH/NiCd batteries.

CC/CV and float charge for Pb batteries.

Reviews

There are yet no reviews for this product.