

Spektrum AR8360T 8 Channel SAFE & AS3X Telemetry



SPMAR8360T

Rating: Not Rated Yet

Price

Sales price R3540,00

[Ask a question about this product](#)

Manufacturer [Spektrum](#)

Description

Compatible with all Spektrum™ DSM2 and DSMX transmitters.

Built in AS3X Stabilization System with SAFE flight envelope protection.

Compact footprint fits most parkflyer size, sport class and giant scale models.

Features full range telemetry, integrated barometer to provide altitude and vario telemetry data without the need of additional sensors.

Bind button allows for easy binding and eliminates the use of bind pins.

In The Box:

(1) AR8360T DSMX 8-Channel AS3X and SAFE Telemetry Receiver

(1) Product Manual

Needed to Complete:

(1) Spektrum Telemetry Capable Transmitter

Overview:

The Spektrum AR8360T 8 Channel AS3X SAFE Telemetry Receiver is a DSM2® and DSMX® capable receiver with a compact footprint to fit in a wide range of aircraft. The AR8360T is a full range 8 channel receiver with built in AS3X stabilization, which counters the effects of wind, turbulence and torque using a 3-axis MEMS gyro and exclusive flight control software tuned by expert RC pilots. There is no delay in control response or limit on control throws. You'll simply feel like you're flying an expertly tuned model that does exactly what you want.

The AR8360T features a full range telemetry, integrated barometer to provide altitude and vario telemetry data without additional purchase. Included XBUS and temperature ports can be used to add additional telemetry sensors available separately. It also features an SRXL2 port for an SRXL2 Remote Receiver (SPM3V47 or SPM4751T), available separately, to add additional RF path redundancy. An SRXL2/Bind Program/Batt servo header is available to connect smart devices, program and update the receiver, bind with a traditional bind plug, or connect a battery. The AR8360T also features a bind button for easy binding with no plugs necessary and offers both SmartSafe™ technology and Hold Last as well as preset failsafe types set through forward programming.

Please Note: The DX7S and DX8 Gen 1 Spektrum Transmitters will not display Altitude or Vario telemetry with the AR8360T receiver.

Please Note: These transmitters do not support Forward Programming devices: DX6i, DX6G2 (EU Version), DX7, DX7S, DX7SE, DX7G2 (EU Version), DX8. Non-computer transmitters.

FEATURES:

Compatible with all Spektrum™ DSM2 and DSMX transmitters.

Built in AS3X Stabilization System with SAFE flight envelope protection.

AS3X and SAFE set up through forward programming directly from your Spektrum transmitter.

Compact footprint fits most parkflyer size, sport class and giant scale models.

Features full range telemetry, integrated barometer to provide altitude and vario telemetry data without the need of additional sensors.

Bind button allows for easy binding and eliminates the use of bind pins.

Two external antennas will ensure secure RF coverage from all angles of the aircraft.

Additional RF path redundancy with an additional SRXL2 Remote Receiver (sold separately).

Ready to use with Spektrum Smart ESC for pre-wire telemetry data without the need of modules, links and wires.

Bind pins output pins for easy and compact installation.

Forward Programming capable for setting individual failsafe parameters per channel and more.

Please Note – Using this receiver in turbine powered aircraft models is not recommended.

Specs:

Application: Airplane, Submarine

Compatible: Yes

Product Weight: 0.56oz (16g)

Channels: 8

Modulation: DSMX

Reviews

There are yet no reviews for this product.